

≡ hoxter ≡



**Woodburning  
Fireplaces**





Since the beginning of time fire has been a place of gathering. It's the heart of the home, where we meet and come back to throughout our lives. Hoxter is inspired by the traditions of yesterday and the needs of today. Resulting in fireplace inserts with clean design, robust construction and innovative technology. Fireplace inserts that transform your living space into a completely unique realization by the best stove makers.





*"Being the best is more important than being the first."*

There are situations where compromise is needed. In others, no compromise can be accepted. We created the company Hoxter ten years ago with a founding principle of no compromise, this principle still stands today. Thanks to this philosophy you will find our products in realizations of the highest technical, aesthetic and functional level.

We are proud to be able to work together with the best stove builders in order to fulfill your dream of a comfortable home. The warmth and fascination of natural fire cannot be replaced by modern technology.

**Petr Banasinski, Richard Dorazil**

Founders of Hoxter

## The best technologies starts with detail

Even the smallest part has its own exact place and function. We create high-quality products thanks to the high quality of materials used and high value human labour. We focus on the needs of the user and a detailed technical performance. Therefore the Hoxter products meet the highest quality standards and offer a maximum user comfort.



**HAKA 89/72**







## **Comfort of clean glass**

Self cleaning fireplace glazing, has a high priority while developing the products Hoxter. The combustion air flow system is designed to lead the air-flow along the fireplace glazing. This air wash creates a dynamic air screen that circulates black combustion particles back into the firebox. The clearness of the fireplace glazing will also be greatly affected by the moisture of the firewood, chimney draught or the way you control the air intake to your fireplace. Consult your local dealer for best practices.

## **Individual design**

Light or dark fireclay lining. Dark fireclay is colored throughout its whole mass not only on the surface. Customizable options that help you create your own handcrafted stove.

The fire clay and refractory concrete materials were cured at 1100 °C (2012 °F). This ensures our refractory will not crack or warp. Hoxter works for all products only with cured materials.











## **Double Ceramic Glass**

Standard for all single face and see-thru models.

The double ceramic glass doors corresponds to current building standards. The double ceramic glass improves the insulation qualities of the door and reduces the heat amount radiated to the room through the door and transfers that heat into the heat exchanger instead. The room with lower energy requirements is not overheated in this way.

## **Guillotine Door Operation (lift door)**

When closing the lift door it is pressed to the body of the fireplace with four springs, each with force of 80 to 250 Newton (8 to 25 kg). The bearings are self greasing and temperature resistant up to 300 °C (572°F).

The door frame is produced from the most heat resistant steel available, with a thickness that far exceeds industry standards. Thanks to this strength, stability is guaranteed on even our large door frames. Our grooved gasket housing ensures that tight door seals are maintain throughout all burn cycles, ensuring the highest overall efficiencies available in the industry.



## Customer service

All Hoxters have been engineered so that all service access is located inside the body of the fireplace unlike most of our competitors, Hoxters NEVER require removal of front facings to gain access to service parts (pulley, cables ect.). Our specially engineered pulleys and cables will ensure that our lift doors will always operate smoothly, even under high heat conditions.





HAKA 89/45th

# Fireplace Flat glass




HAKA **63/51**

Heat output range **6–16 kW**

Amount of firewood per heating cycle **6 kg**

Ratio heat distribution




HAKA **78/57**

Heat output range **6–16 kW**

Amount of firewood per heating cycle **5,5 kg**

Ratio heat distribution




HAKA **78/57h**

Heat output range **6–16 kW**

Amount of firewood per heating cycle **5,5 kg**

Ratio heat distribution




HAKA **89/72h**

Heat output range **9–18 kW**

Amount of firewood per heating cycle **5,5 kg**


Ratio heat distribution



HAKA **110/51h**

Heat output range **9–18 kW**

Ratio heat distribution



HAKA **150/51h**

Heat output range **10–20 kW**

Ratio heat distribution



The technical data and drawings are to be found on our homepage [www.hoxter-fireplaces.com](http://www.hoxter-fireplaces.com)

- Fireplace (+ attached storage mass)
- Door glass (double glazing)

# Fireplace See-thru




HAKA 78/57Th

Heat output range **6–16 kW**

Amount of firewood per heating cycle **6 kg**

Ratio heat distribution



HAKA 110/51Th

Heat output range **9–18 kW**

Ratio heat distribution



# Fireplace Corner glass




ECKA 51/51/51

Heat output range **5–13 kW**

Amount of firewood per heating cycle **5 kg**

Ratio heat distribution



Coming  
2022/23

ECKA 67/45/51h

Heat output range **6–16 kW**

Amount of firewood per heating cycle **5,5 kg**

Ratio heat distribution



# Fireplace Three side glass




UKA **37/55/37/57h**

Heat output range **6–12 kW**

Amount of firewood per heating cycle **4 kg**

Ratio heat distribution



UKA **37/75/37/57h**

Heat output range **8–14 kW**

Amount of firewood per heating cycle **4,5 kg**

Ratio heat distribution




UKA **37/95/37/57h**

Heat output range **9–17 kW**

Amount of firewood per heating cycle **5 kg**

Ratio heat distribution



UKA **56/50/56/52h**

Heat output range **5–12 kW**

Amount of firewood per heating cycle **4,5 kg**

Ratio heat distribution




UKA **86/50/86/52h**

Heat output range **8–15 kW**

Amount of firewood per heating cycle **5 kg**

Ratio heat distribution



The technical data and drawings are to be found on our homepage [www.hoxter-fireplaces.com](http://www.hoxter-fireplaces.com)

■ Fireplace (+ attached storage mass)  
■ Door glass (single glazing)

## Handles and frames



Removable handle



Casing for the removable handle



Cover frame 2 x 45°



Cover frame 1 x 90°



Cover frame 1 x 90° (ECKA)



Build-on frame 50 mm

## Hoxter reliability

5 year warranty for the body and 2 years for all components.

\*please note - shown stainless steel handle not available for the US market

HAKA 150/51 – Jinacovice – Czech Republic **1**  
UKA 56/50/56/52 – Brno – Czech Republic **2–3**  
HAKA 89/72 – Helsinki – Finland **6–7**  
UKA 86/50/86/52 – Passau – Germany **8–9**  
HAKA 150/51 – Jinacovice – Czech Republic **12–13**  
HAKA 89/72 – Trojanovice – Czech Republic **14–15**  
HAKA 110/51T – Brno – Czech Republic **16–17**



**Hoxter GmbH**

Haidmühlweg 5  
92665 Altenstadt an der Waldnaab  
GERMANY  
Tel.: +49 (0)9602 944 7944  
E-mail: [info@hoxter.de](mailto:info@hoxter.de)

**Hoxter a.s.**

Jinacovice 512  
66434 Jinacovice  
CZECH REPUBLIC  
Tel.: +420 518 777 701  
E-mail: [info@hoxter.eu](mailto:info@hoxter.eu)

**[www.hoxter.eu](http://www.hoxter.eu)**

**[www.hoxter-fireplaces.com](http://www.hoxter-fireplaces.com)**

**Imported by Vulcan Group – USA & Canada**



100 West Main St  
Plantsville, Connecticut  
06479  
UNITED STATES  
Tel.: (860) 639-8284  
E-mail: [info.thevulcangroup@gmail.com](mailto:info.thevulcangroup@gmail.com)  
**[www.thevulcangroup.com](http://www.thevulcangroup.com)**

**Version 09/2021**

Changes of the stated data and errors reserved.

The technical data and drawings are to be found on our homepage **[www.hoxter-fireplaces.com](http://www.hoxter-fireplaces.com)**